

SAFETY & CONVENIENCE,
MANDO+



MEISTER Global Headquarters
Seoul, Korea

13th. Fl. Luther Center. Bldg.
7-20 Sincheon-dong, Songpa-gu,
Seoul 138-240, Korea

Tel : (82)-2-526-0625
Fax : (82)-2-526-0599
E-mail : contact@mandoplus.com

www.meister.co.kr



MANDO+

MANDO 2012 National Brand Awards

MANDO awarded '2012 National Brand Awards'
in the category of Autoparts



An aftermarket automotive parts brand of Meister, MANDO PLUS, is based on the trust in supreme quality.

We play a pivotal role in the distribution of MANDO's various OE products, recognized for their advanced technology and premium quality not only by Korean auto manufacturers but also by the top auto makers worldwide, reaching both domestic & overseas markets.

Besides MANDO products, Meister has been supplying the global market with various outsourced items of OE quality.


MANDO PLUS is aimed at providing Meister's customers worldwide with more opportunities to make access to supreme quality products with much wider product range, which have passed the stringent quality assurance test of Meister.

MANDO PLUS

ENGINE OIL



ENGINE OIL | MISSION OIL

 **MANDO** awarded '2012 National Brand Awards'
in the category of Autoparts

TB C3

TB C3 is specially formulated for the lubrication needs of modern gasoline and diesel cars and RV/SUV with DPF. Formulated with advanced base stocks, premium additives.

TB C3 contains high quality anti-wear additives and surpasses the tough ACEA oil specifications for high temperature/high shear viscosity. It provides outstanding protection in high RPM, hot running engines.

TB C3 is recommended specially for diesel engines with the after-treatment system which fulfill the EURO IV.

TB C3 holds the effectiveness of the after-treatment system for very long term.

| Performance Level | Viscosity Grade |
|---------------------------------|-----------------|
| API SM/CF, ACEA C3, A3/B4 | SAE 5W30 |
| MB 229.51, VW 50200/50500/50501 | |
| BMW LL-04 | |

Features

- Reduced evaporation tendency
- Very good cold start properties
- Very good protection against sludge
- Reduced wear of cylinder and camshaft
- Reduced fuel consumption thanks to smooth running properties



ENGINE OIL



TB SUV

TB SUV is a full synthetic motor oil that is formulated with high quality synthetic base oils and enhanced with most advanced additive technology for ultimate performance in meeting the latest requirement for modern engines.

TB SUV motor oil provides protection under severe service conditions and meet the performance requirement of turbo-charged, supercharged passenger cars, RV and SUV.

Features

- Breakdown Resistance : Increased thermal and oxidation stability.
- Deposit Control : Reduces formation of sludge and varnish deposits.
- Wear Protection : Improves oil film strength and breakdown resistance.
- Cold Start Properties : Flows easily at low temperature.

| Performance Level | Viscosity Grade |
|---|-----------------|
| API SM/SL/CF, ACEA A3/B3/B4 MB 229.3/229.1, VW 502 00/505 00 | SAE 5W40 |



TB X

TB X is formulated with a combination of high-tech synthetic and premium quality base stocks combined with advanced additive technology.

TB X can help engines maintain peak performance longer by providing improved wear control, deposit protection, volatility, and low temperature flow characteristics versus conventional motor oils.

Advantage

- Breakdown Resistance: Increase thermal and oxidation stability
- Deposit Control: Reduces formation of sludge and varnish deposits
- Wear Protection: Improves oil film strength and breakdown resistance
- Volatility: Lowers oil vaporization and consumption at extreme temperature

| Performance Level | Viscosity Grade |
|-------------------|-----------------|
| API SN | SAE 5W40 |



MANDO awarded '2012 National Brand Awards' in the category of Autoparts

TB DIESEL

TB Diesel is a super-premium heavy duty diesel engine oil formulated to provide optimum performances in modern, low emission diesel engines operating under a wide variety of service conditions. This oil is blended with premium basestocks and high quality additive chemistry to achieve the following benefits: high temperature piston deposit control, foam protection, soot dispersancy and oil-thickening control, oxidation inhibition, low temperature sludge protection, corrosion and rust inhibition, valve train wear protection and TBN retention.

TB Diesel is recommended for use in turbocharged and naturally aspired two and four cycle diesel engines. They may also be used in gasoline engines for the "mixed fleet" operator. This motor oil provide excellent performance in local stop and go routes, on-and off-highway, farm, construction, and mining applications.

| Performance Level | Viscosity Grade |
|---|-----------------|
| API CI-4/CH-4/CG-4/CF-4/CF/SL ACEA E7/B3/B4/A3, MB 228.3/229.1 Cummins CES 20071/72/76/77/78 MAN 3275, MTU Type 2, Volvo VDS-3 Mack EO-M Plus, Renault RLD/RLD-2 CAT ECF-2/1-a, ZF TE-ML 07C | SAE 15W40 |



MISSION OIL

ATF SPECIAL

ATF SPECIAL is recommended for lock-up clutch vehicles.

ATF SPECIAL meets the latest "H" version of the licensing.

ATF SPECIAL is formulated with synthetic base oil and advanced additive technology to meet the challenging demands of an automatic transmission environment.

ATF SPECIAL is a high quality friction modified lubricant qualified by both General Motors and Ford. Its responsive low temperature fluidity is beneficial in both electronic and hydraulic controlled transmissions and transaxles. It may be used for service fill where Mercon, Dexron, Dexron II or Dexron IIE is recommended.

Performance Level

Dexron III(H), Mercon
HYUNDAI/KIA - SPII, SPIII



MANDO awarded '2012 National Brand Awards' in the category of Autoparts

ATF DEX / MERC

ATF DEX/MERC meets the latest "H" version of the licensing.

ATF DEX/MERC is formulated with premium base stocks and advanced additive technology to meet the challenging demands of an automatic transmission environment.

ATF DEX/MERC is a high quality friction modified lubricant qualified by both General Motors and Ford. Its responsive low temperature fluidity is beneficial in both electronic and hydraulic controlled transmissions and transaxles. It may be used for service fill where Mercon, Dexron, Dexron II or Dexron IIE is recommended.

Performance Level

Dexron III(H), Mercon
Allison C-4



MANDO+

